

New Draft Schedule




Chamber






Translation plates I



Repère	Nom	Quantité	Etat
1	chassis Riken/ Riken frame	1	
2	platine réglage chambre type	1	
	1/ adjustment plate 1		
3	platine réglage chambre type 2	1	
	/ adjustment plate 2		
4	platine réglage chambre type 3	1	
	: adjustment plate 3		
5	platine roue droite / right	2	
	wheel frame		
6	platine roue gauche / left	2	
	wheel frame		

	10	I.	9	ı	8	, 1	7
	_	lodficetore				Date	Indios
□			10/2000	RS	ndel.	NP.	GATTA WS
		N' ensemble	Cate	Deed	né par	Wedde par	Logistei
	100 100	$\overline{}$					3 2

Translation plates details




Repère		Quantité	
1	Plaque fixe translation type 1 /	2	New
	fixed plate 1		
2	Plaque fixe translation type 2 /	1	New
	fixed plate 2		
3	plaque de poussée / push plate	7	New
4	platine réglage translation /	3	New
	translation plate		
5	rondelle plate d13 x d35 x 3 /	3	New
	washer		
6	rondelle concave d24 / concave	3	
	washer d24		
7	rondelle convexe d24 / convex	3	
	washer d24		
8	écrou M24/ Nut M24	9	
9	cale de poussée type 1/spacer 1	2	New
10	cale de poussée type 2 / spacer	4	New
	2		
11	vis Chc M12 x 30 / screw	12	
12	vis H M10 x 90 / screw	12	
13	vis Chc M12 x 50 / screw	12	
14	rondelle plate d12 / washer	24	
15	écrou M12 /nut	12	

Can RIKEN get this machined or get it from MUST-II group?





Chamber: bottom plate design



Microball Analysis

- Determination of b using N_C
- Requires downstream scintillator to normalize beam counts





Preparation To Be Completed

- Chamber
 - Translation plates -- Aki
- Microball Mount Design (Who can sketch this up?)
 - Microball should be centered on beamline (splitting rings apart)
 - Make a bar that can be used for design and testing easily
 - Platform mounts to center flange
 - Target drive mechanism moves from underneath
 - Attach collimator on platform
- Sn Target Ladder Design (Aki)
 - Moves between the two halves of microball
 - Need enough room below microball platform for ladder length to move in/out of beamline
 - Rachel will roll out targets this week
- Scintillator/beam counter downstream of target (Rachel)
 - Design of movable platform
- Need to buy two target mechanisms, remote controlled (Aki)

Preparation To Be Completed, continued

- Cables: (Can we get something for Aki to check this out or sketch out in the drawing?)
 - Length depends on position of microball, scintillator and distances to flanges
 - May need cable extenders for microball
- Electronics (Alfredo, when can this be sent to RIKEN?)
 - WU preamps mounted outside chamber
- Flanges: What type of flanges we can borrow from MSU? (This week)
- Adapters for flanges: based on cables used, designs of microball and scintillator platforms, preamps mounted to outside
- Machining:
 - Microball platform mount
 - Scintillator platform
 - Flange adaptors as needed

Rough Timeline

- February 15: finalize the design of the inside of chamber
- March 1: finalize design of target ladder
- April 1: start to order machining and other devices
- April 1: start to test electronics
- May 7: start to mount the detectors in chamber
- May 27: ready to install vacuum chamber to F8, check alignment. (Need to move the date in view of new schedule)
- June 10-15: Experiment runs (official as of Jan 28)
- June 27: User Meeting